



The Loft 2006 TRIM GUIDE

Table of contents

	Page
Intro	2
Downhaul	2
Outhaul	2
Rig Trim Optimization	3
Boom Height	3
Harness lines	3
-Position	3
-Length	3
-Harness type	4
Batten Tension	4
Masts	4
Board trim	4
-Footstraps	4
-Fins	4
-Mastfoot	5
High wind trim package	5
Low wind trim package	5
Troubleshooting	5
The Loft 2006 sail specifications	6&7

Trim Intro

Windsurfing rigs have by an elastic, living character... the aerodynamic form your sail presents to the wind depends primarily on three elements:

- sail design (mast and seam curves cut into the sail),
- mast stiffness/flex character
- the trim you set into your rig (downhaul & outhaul tension as well mast-foot position and boom-height, among other trim settings).

Performance & wind range expansion = trim sensitivity

Loftsails are exceptionally trim response.

Trim begins with noting the boom length, mast length and the recommended mast which is printed on your sail and sailbag.

Rig trim is *critical* to rig performance.

The rig reacts directly to the two primary trim variables: downhaul and outhaul tensions.

DOWNHAUL

All sails respond favorably to increased downhaul tension for high wind sailing. For strong winds it pays to be radical... **increased downhaul tension** will produce **easier handling and greater speed** in strong winds.

An 8:1 tack pulley system is recommended for easy application of the high downhaul tension needed for strong wind performance.

When overpowered- tension the downhaul! High downhaul tension will open the sail's leech (rear edge), releasing sail power. High downhaul tension will also flatten the sail body making the rig significantly easier to handle in strong wind and increase your speed and fun! Be aggressive with downhaul tension as the wind rises...

Loftsails are built to accept & respond to high downhaul tension which will soften the leech from the head all the way down to the boom

- correct trim if your sail feels too powerful.

Should the wind drop, or should you find your sail size small for the wind strength, **less downhaul** tension will firm up the leech and make the sail body fuller. Such reduced, or "soft" trim will generate **greater low-end power**.

When winds are sufficient for easy planning, it is the right moment to experiment with increased downhaul tension. The feeling of free speed will set your windsurfing soul free! The adjustment range between ideal low wind trim and ideal high wind trim for a given sail size may be as much as 5cm.

OUTHHAUL

The **outhaul** has direct impact on rig performance. **Reduced** outhaul makes the sail deeper in profile generating **greater power** for light winds. Extreme low wind trim will increase light wind power and also make the rig feel stiff and more back hand oriented, especially should the wind rise.

Greater outhaul tension flattens the sail profile making the sail much **easier to handle** and faster in medium and strong winds. Flatter outhaul trim allows the

sail to pass more easily through the wind. For a given sail size the range between ideal strong and light wind trim may be up to 6cm.

An easy outhaul **trim reference** is the forward end of the batten just above the boom. If this forward batten end passes the mast without touching the mast the outhaul is set well for medium-to-high winds. If this batten end makes mast contact during rotation the outhaul is set for light-to-medium winds. Note that downhaul tension will influence this trim reference as well as outhaul tension.

Optimizing rig trim goes beyond outhaul and downhaul sail adjustments. Boom height, the mastfoot position, harness lines and mast type all impact your windsurfing performance.

-Boom height has a direct performance impact. Low boom height will make initiation of planing difficult. An overly high boom promotes early tail walking and makes maneuvers difficult; a good position to begin is **chest/shoulder level**.

In very light winds the boom is best raised to assist in the initiation of planing. A higher boom places more of the windsurfer's weight onto the rig and less on the board, consequently the board has a greater capacity to lift and plane. If the wind is strong for your sail size lowering the boom will give the windsurfer greater control. With a lower boom position the riders' weight becomes more board oriented; increasing board control in challenging conditions.

-Harness lines are your power transfer: their **position** and length will affect rig performance. The harness lines bear the diving power from the rig allowing the windsurfer to be free! Finding the right harness line position is a question of balance. Windsurfers who are starting with the harness usually like to place the lines too far forward reducing the likelihood of being catapulted. Lines too far forward will limit speed as the windsurfer is kept forward, forcing more board into the water.

To place the lines correctly go with the flow... if harness lines are too far forward the back arm becomes fatigued. If the lines are too far back the forward arm becomes fatigued. Try sailing with no hands! When the lines are placed correctly you will be able to sail for long moments with no hands! If you reach for the boom first with your backhand the lines should be moved back. If you reach for the boom first with the front hand the lines should be moved forward.

Lines placed further apart on the boom may produce a feeling of greater stability. Wide line placements (30cm+) will transfer sail power comfortably and are generally better suited to beginning and intermediate windsurfers.

Narrow harness lines (12cm and less) transfer power to the sailor more directly, more critically. As the harness lines are placed closer together on the boom they make rig trim more critical relative to the power center. Racers set extremely narrow harness line placement.

-Harness line length also influences performance. For average size windsurfers **26cm** to 28 cm from the line center to the boom is an average harness line length.

Short lines limit speed potential... bodyweight is the power generator.

Bodyweight too close to the rig and maximum power is unavailable. Overly short lines (less than 25cm max from boom) limits the reaction time as the windsurfer encounters changing wind and sea conditions. Overly long lines

(more than 32 cm) may cause arm fatigue and rather wet windsurfing as the sailor may make contact with the water.

Correct harness line position is affected by downhaul and outhaul tension; strong wind trim will shift the harness line positions forward; light wind trim will bring the harness lines further back, the difference being in the range of 2-4 cm regarding harness line position.

-Harnesses A loose fitting harness affects negatively harness function; power transfer is less effective and is detrimental to your windsurfing performance.

Keep your harness tight!

Waist-type harnesses are generally used for wave and freestyle windsurfing, such locate the hook higher on the body; suitable for maneuver-ease.

Racing/slalom/speed harnesses are normally lower on the body, bringing the hook down which more easily closes the rig down onto the board. Low harness hooks generally make more available power from the rig, augmenting speed potential.

Harness type can influence harness line length. Wave harnesses (waist type) seem to prefer shorter lines, while slalom/racing harnesses (seat type) are normally associated with longer harness lines.

-Batten tension is simple! Tension the battens until the sail becomes visibly taught. Many windsurfers overlook batten tension. Full batten tension **makes the rig more stable** as well as removing wrinkles. Severe over tensioning battens may cause asymmetric profiles and affect batten rotation. Cammed battens may need special care as over tensioning cammed battens may result in hard rotation.

-Masts influence rig performance. It is best to use the recommended mast for your sail.

If a **softer** mast is used the rig becomes more flexible; rig handling will normally become easier in **high winds** and the rig will be easier to close down onto the board ("closing the gap"). Softer masts will normally make the rig faster downwind.

A **stiffer** mast will have the opposite effect; the rig will become more difficult to close down onto the board in the upper wind range. Stiffer masts tend to go **upwind** more efficiently compared to soft masts.

BOARD TRIM

Boards have three trim variables; footstraps, fins and mastfoot position.

-Footstrap position determines the sailor's stance on the board and therefore the board's attitude in the water. Most boards have options regarding footstrap placement. Generally, a **wide** stance is **control and maneuver** oriented. For rough water/upper end conditions, footstraps placed forward and farther apart will result in more control over the board and the lift generated by the fin.

On **flat water** footstraps may be best located further **back**. Rear footstrap positions, and straps set closer together will allow the windsurfer to **fly more** on the fin with less board in the water for greater speed potential.

-Fins Deeper/bigger fins are well suited for **light winds** as they generate greater lift at lower speeds. As the wind rises **shorter fins** will make the board **easier to handle**. The fins angle to the bottom of the board will also affect performance.

Vertical fins will make the board fly; better for lighter winds and speed.

Sweptback fins will make the board easier to control in stronger winds and generally turn more easily but may detract from light and medium wind speed performance.

-The Mastfoot is where the power and the ride meet, so position is critical!. Generally, forward placement increases board control by taking the sailor's weight forward, more onto the board, controlling the fin. **Rear** mastfoot positions are more speed oriented as the fin is allowed greater ability to lift the board; with more of the board out of the water **speed** potential is increased. The mastfoot set 137-140cm from the tail is a good "all-round" position from which to begin.

High wind trim package

If you feel overpowered set the mast and boom length to the recommended high-wind lengths and trim accordingly. Also try the boom lower by 2-4 cm and set the mastfoot further forward 1-3cm. Hi wind trim will require the harness lines to move forward by 2-4cm compared to low wind trim.

Low wind trim package

To trim for power free the downhaul and the boom 2-4cm. Raise the boom a few centimeters and move the mastfoot back 2 – 3 cm. Low wind trim will require the harness lines to move back by 2-4cm compared to high wind trim.

Experience the new sensations resulting from trim alternatives, and you will **expand your windsurfing performance!**

Troubleshooting

Windsurfing is a wonderful feeling of balance. Should you feel unbalanced try one or more of the solutions listed. One of the solutions or a combination of them may bring balance for you!

⊗The rig feels stiff and heavy with too much backhand power.
 ☺Try more downhaul, more outhaul, mastfoot back, boom up.

⊗The board has the tendency to turn into the wind.
 ☺Try the mastfoot further forward, harness lines further back, footstraps further forward.

⊗The board has the tendency to turn downwind.
 ☺Try the mastfoot farther back, higher boom, harness lines further forward, bigger fin, footstraps farther back.

⊗The windsurfer feels in constant danger of being catapulted.
 ☺Try more downhaul, harness lines farther forward and farther apart, smaller sail, more outhaul, softer mast.

⊗Slow, stuck to the water feeling.
 ☺Try the mastfoot farther back, boom higher, more downhaul, harness lines farther back and closer together, bigger fin, footstraps farther back, bigger sail.

⊗Difficulty to get planning.
 ☺Try the boom higher, mastfoot farther back, bigger fin, bigger sail, harness lines back, less outhaul, footstraps farther back.

⊗The board stands on the tail in strong winds (tailwalking).
 ☺Try more downhaul, more outhaul, mastfoot farther forward, smaller fin, footstraps farther forward, softer mast.

⊗The board spins out easily.
 ☺Try more downhaul, more outhaul; straps further forward, bigger fin, mastfoot further back, softer mast.

⊗Difficulty closing the sail down onto the board.
 ☺Try more outhaul, more downhaul, mastfoot further forward, smaller fin, softer mast, footstraps farther back, harness lines farther back, lower harness hook, smaller sail.

⊗The board bounces in chop and when starting to gibe.
 ☺Try the mastfoot farther forward; boom lower, more downhaul, more outhaul, smaller fin, footstraps farther forward, smaller sail.

Optimizing trim for **high performance windsurfing** is a process that has no limits! Improvements in one area will compliment trim improvements in other areas. Performance can always be expanded as new, more efficient trim configurations are experienced. Maximizing trim is the cutting edge of windsurfing. Windsurfing is the most efficient purest sailing form... a never-ending source of new sensations...
Experience it!

THE LOFT · 2006 sail specifications

(All lengths in cm)

Lip Wave Concept - Hardcore wave

Size m ²	Mast	Boom	Recom. Mast	IMCS	Mast Ext.	Vario Top	Battens	Cams	Micro Battens	Weight Kg
5.7	446	185	430 Rdm	21	16	0	5	0	2	3.83
5.2	425	177	400 Rdm	19	25	0	5	0	2	3.68
4.7	404	167	400 Rdm	19	4	0	5	0	2	3.50
4.3	387	158	370 Rdm	17	17	0	5	0	2	3.35
3.9	370	150	370 Rdm	14	0	0	5	0	2	3.17
3.5	347	145	340 Rdm	14	7	0	5	0	2	2.86
3.1	330	144	340 Rdm	14	0	10	4	0	2	2.59

Lip Freewave Concept - Freestyle / Light-wind wave

Size m ²	Mast	Boom	Recom. Mast	IMCS	Mast Ext.	Vario Top	Battens	Cams	Micro Battens	Weight Kg
6.8	476	202	460 Rdm	25	16	0	5	0	2	4.30
6.2	460	191	430 Rdm	21	30	0	5	0	2	4.10

O2 Freeride Concept - Freeride / Slalom-speed

Size m ²	Mast	Boom	Recom. Mast	IMCS	Mast Ext.	Vario Top	Battens	Cams	Micro Battens	Weight Kg
7.4	488	218	460 Rdm	25	28	0	⁶ (4 tubed)	0	4	4.59
6.6	470	203	460 Rdm	25	10	0	⁶ (4 tubed)	0	4	4.36
5.9	446	190	430 Rdm	21	16	0	⁶ (4 tubed)	0	4	4.07
5.3	426	182	400 Rdm	19	26	0	⁶ (4 tubed)	0	4	3.96

O2 Freerace Concept – Freeride / Race wideboards

Size m ²	Mast	Boom	Recom. Mast	IMCS	Mast Ext.	Fixed top	Battens	Cams	Micro Battens	Weight Kg
10.8	562	267	550 Ndm	38	12	x	7 (6 tubed)	0	5	5.98
9.6	532	245	520 Ndm	34	12	x	7 (6 tubed)	0	5	5.54
8.4	513	229	490 Ndm	29	23	x	7 (6 tubed)	0	5	5.18

Concept 360 – All-round performance, easy & light

Size m ²	Mast	Boom	Recom. Mast	IMCS	Mast Ext.	Vario Top	Battens	Cams	Micro Battens	Weight Kg
5.8	435	195	430 Rdm	21	5	0	5	0	2	3.61
5.1	412	186	400 Rdm	19	12	0	5	0	2	3.40
4.5	372	174	370 Rdm	17	2	0	4	0	2	2.87
4.0	354	160	340 Rdm	14	14	0	4	0	2	2.67
3.5	340	150	340 Rdm	14	0	0	3	0	2	2.35

All sails include the "Sensitip" head batten system except the Lip Wave Concept 3.5 & 3.1 and all Concept 360 sizes.

Mast & boom measurements are trim settings for high winds. Reduce for lighter winds.

All specs subject to change without notice.

Tarifa, August 2005

Kids

Size	Mast	Boom	Mast Rec.	Compatible masts
Spark 3.2	370	150	370 rdm sdm alu	350 rdm sdm alu
Kiddo 2.5	370	150	370 rdm sdm alu	350 rdm sdm alu

All measurements in centimeters. Mast & boom measurements listed are trim settings for high winds. Reduce for lighter winds.

The Loft, February 2006

www.loftsails.com

Specifications subject to change without notice.

Questions and/or comments welcome monty@loftsails.com